HIGH-PERFORMANCE FAST CAMERAS



FAST M350



HIGH-SPEED VGA-FORMAT SCIENTIFIC THERMAL IMAGING

KEY FEATURES



HIGH FRAME RATE



HIGH-SPEED INTERNAL MEMORY



HIGH SENSITIVITY



ADVANCED CALIBRATION

The FAST-IR series includes the fastest infrared cameras available on the market. The M350 is a cooled, high-performance scientific thermal infrared camera designed to provide excellent image quality and impressive thermal sensitivity. It features our unique real-time calibration and is an excellent choice for a variety of scientific and industrial applications.

exosens.com

FAST M350





Jet Engine IR Signature Measurement

Target Ranging

SPECIFICATIONS	
Detector Type	Cooled InSb
Detector Format	640 x 512 pixels
Spectral Range	1.5 – 5.4 μm
Detector Pitch	15 μm
Aperture Size	F/3 (other available)
Typical NETD	20 mK
Exposure Time	0.5 µs to full frame rate
Frame Rate	355 Hz
Maximum Frame Rate	672 Hz @ 320 × 256 4 980 Hz @ 132 × 4
Environmental Resistance	IP67
Operational Shock	IEC-60068-2-27
Operational Vibration	IEC-60068-2-64
Operational Temperature	-20 °C to +55 °C
Storage Temperature	-40 °C to +70 °C
Lens Mount	Bayonet

sales@telops.com



exosens.com



© Telops. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Telops group of companies nor by any Exosens Group companies. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current product information from the Telops group of companies before placing orders. Texts and pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Telops.

in 🛗 f 🎯