

**HIGH-PERFORMANCE
FAST CAMERAS**

TELOPS
EXOSENS GROUP

FAST M200hd



*HIGH-SPEED HD-FORMAT
SCIENTIFIC THERMAL IMAGING*

KEY FEATURES



HIGH DEFINITION



**HIGH SPATIAL RESOLUTION AND
IMAGING QUALITY**



WIDE SPECTRAL BAND




ADVANCED CALIBRATION

The M200hd is a cooled, high-performance scientific thermal infrared camera designed to provide excellent image quality and impressive thermal sensitivity. It features our unique real-time calibration and is an excellent choice for a variety of scientific and industrial applications.



FAST M200hd



Experimental Mechanics



Target Ranging

SPECIFICATIONS

Detector Type	Cooled InSb
Spectral Range	1.5 μm to 5.4 μm (3 to 5 μm optional)
Spatial Resolution	1 280 \times 1 024 pixels
Detector Pitch	10 μm
Aperture Size	F/3
Maximum Frame Rate (Full Window)	180 Hz
Maximum Frame Rate (Subwindow)	3 521 Hz @ 64 \times 8
Typical NETD	30 mK
Minimum Exposure Time	0.5 μs to full frame rate
Lens Mount	Bayonet

sales@telops.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE

© Telops. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Telops group of companies nor by any Exosens Group companies. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current product information from the Telops group of companies before placing orders. Texts and pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Telops.